

4

3

2

1

CONFIDENTIAL AND PROPRIETARY TO
KZCO, INC. UNAUTHORIZED USE, DISCLOSURE
OF REPRODUCTION IS PROHIBITED

FOR MORE DETAILS AND INFORMATION, CONTACT: SALES@KZCO.COM

4.0

7.4

3.0

$\phi .4$

5.7

8.1

2.4

1/2" NPT

CONFORMS TO ASME
STANDARDS Y14.5-2009

-STANDARD TOLERANCES- -ALL DIMENSIONS IN INCHES [mm]- .X±0.1 .XX±0.001 .XXX±0.005 .X°±1°	TOTAL RUNOUT: .005 FIM CORNER BREAK: .001/.010 SURFACE FINISH: 125 μIN 	DESIGNED BY: Brian Pham		23860 KZ PARKWAY GREENWOOD, NE 68366 USA PHONE: +1.402.944.2767 FAX: +1.402.944.2402
		DRAWN BY: Aaron Goodwin		
DENSITY: 0.133 LBM/CU IN MASS: 4.407 LBM SURF AREA: 512.368 SQ IN VOLUME: 33.068 CU IN		APPROVED:	TITLE: ACTUATED VALVE, EH3, 1/2" FP 3-WAY SS, OFFSET MOUNT, ON/OFF 0.8 SEC@12VDC	
		SCALE: 2:3	PART NO: 73D23-10D20-P31	REV: 1
		SIZE: B	DRAWING NO: SALES_73D23-10D20-P31	SHEET: 1 OF 1
		MATERIAL: AS NOTED		

4

3

2

1