

4

3

2

1

CONFIDENTIAL AND PROPRIETARY TO KZCO, INC. UNAUTHORIZED USE, DISCLOSURE OF REPRODUCTION IS PROHIBITED

FOR MORE DETAILS AND INFORMATION, CONTACT: SALES@KZCO.COM

4.0

$\phi .4$

1/4" NPT

1.2

5.7

7.5

$\phi 1.2$

2.4

2000 CWP

<p>-STANDARD TOLERANCES- -ALL DIMENSIONS IN INCHES [mm]-</p> <p>.X±0.1 .XX±0.001 .XXX±0.005 .X°±1°</p>		<p>DESIGNED BY: Tanner Buresh</p>	<p>KZCO inc.</p> <p>23860 KZ PARKWAY GREENWOOD, NE 68366 USA PHONE: +1.402.944.2767 FAX: +1.402.944.2402</p>	
<p>TOTAL RUNOUT: .005 FIM CORNER BREAK: .001/.010 SURFACE FINISH: 125 µIN</p> <p></p> <p>DENSITY: 0.089 LBM/CU IN MASS: 2.643 LBM SURF AREA: 451.615 SQ IN VOLUME: 29.700 CU IN</p>		<p>DRAWN BY: Aaron Goodwin</p> <p>APPROVED:</p> <p>SCALE: 2:3</p> <p>SIZE: B</p> <p>MATERIAL: Material <not specified></p>		<p>TITLE: ACTUATED VALVE, EH3, 1/4", SS 2-WAY, INLINE MTG ON/OFF 0.8 SEC @ 12VDC, 3ST WP3T</p>
<p>CONFORMS TO ASME STANDARDS Y14.5-2009</p>			<p>PART NO: 88B33-10D20-P01</p> <p>DRAWING NO: SALES_88B33-10D20-P01</p>	<p>REV: 1</p> <p>SHEET: 1 OF 1</p>

4

3

2

1