

4

3

2

1

CONFIDENTIAL AND PROPRIETARY TO
KZCO, INC. UNAUTHORIZED USE, DISCLOSURE
OF REPRODUCTION IS PROHIBITED

FOR MORE DETAILS AND INFORMATION, CONTACT: SALES@KZCO.COM

4.4

8.4

3.4

1
CFM

7.2

7.5

1" NPT
BOTH SIDES

Ø.9

CONFORMS TO ASME
STANDARDS Y14.5-2009

-STANDARD TOLERANCES- -ALL DIMENSIONS IN INCHES [mm]- .X±0.1 .XX±0.001 .XXX±0.005 .X°±1°	TOTAL RUNOUT: .005 FIM CORNER BREAK: .001 / .010 SURFACE FINISH: 125 µIN 	DESIGNED BY: Brian Pham		23860 KZ PARKWAY GREENWOOD, NE 68366 USA PHONE: +1.402.944.2767 FAX: +1.402.944.2402
		DRAWN BY: Aaron Goodwin		
DENSITY: 0.064 LBM/CU IN MASS: 3.007 LBM SURF AREA: 647.831 SQ IN VOLUME: 47.297 CU IN		APPROVED:	TITLE: ACTUATED VALVE, EH22, 1", SS 2-WAY, OFFSET MTG, ON/OFF, 1.5 SEC @ 12VDC, 3ST WP3T	
		SCALE: 1:2	PART NO: 88F22-10DY0-PF1	REV: 1
		SIZE: B	DRAWING NO: SALES_88F22-10DY0-PF1	SHEET: 1 OF 1
		MATERIAL: Material <not specified>		

4

3

2

1