CONFIDENTIAL AND PROPRIETARY TO KZVALVE, LLC. UNAUTHORIZED USE, DISCLOSURE OR REPRODUCTION IS PROHIBITED

DESIGN NOTES:

PART NUMBER: NPZC28-1CEBS-D01 1.

4

- **KZVALVE ACTUATOR SERIES: EH8** 2.
- 3. ACTUATION TIME @ 90 DEGREES: 0.2S @ 12VDC
- AMBIENT OPERATING TEMP: -40°F TO 185°F (-40°C TO 85°C) 4.

3

3

- AMBIENT STORAGE TEMP: -67 °F TO 221 °F (-55 °C TO 105 °C) 5.
- ENCLOSURE RATING: IP68 PER ISO 20653, NEMA 6P/7D PER 6. NEMA 250
- 7. UP TO 90 DEG OF TOTAL TRAVEL - ROTATION TO OPEN STATE IS CLOCKWISE WHEN VIEWED FROM THE BOTTOM SIDE
- 8. ELECTRICAL

В

А

- **OPERATING INPUT VOLTAGE: 9-32 VDC** Ι.
- 2. CURRENT DRAW
 - NORMAL OPERATION: 0.4 AMPS @ 12 VDC 1
 - CONTINUOS (RUNNING STATE): 0.04 AMPS 2.
 - 3. STALL (LOCKED ROTOR): 1.8 AMPS @ 12 VDC CONNECTION: 4-PIN DEUTSCH RECEPTACLE


 - PIN MATERIAL: GOLD-PLATED BRASS 1.
 - PINOUT 4.
 - PIN 1 POWER IN (-) ١.
 - PIN 2 FEEDBACK (+) AT OPEN 2.
 - 3. PIN 3 - SIG 1 (+) AT ÓPEN
 - PIN 4 POWER IN (+) 4.

4

9. VALVE

3.

- 5. WETTED MATERIALS: FKM, CG REINFORCED PTFE, NYLON, 316SS
- MAX PRESSURE DIFFERENTIAL: 150 PSI @ 70°F



0 00 43 1.7 •)

0

2

2

REV	ECN	
1	24-0723	

CUSTOMER REVISIONS		
	CHANGE	MODIFIED BY
CREATED CUSTOMER SHEET		Austin Gemar

1

В

Α